

Platformate

Use: High octane component for gasoline blending

Shipping: By tank trucks and tankers



Properties	Unit of measure	Test method
Research octane number (RON)	-	BAS ISO 5164:2005
Motor octane number (MON)	-	BAS ISO 5163:2005
Led content	mg/l	BAS EN 237:2006
Density at 15°C	kg/m ³	BAS EN ISO 3675:2004 BAS ISO 12185:1996/Cor.1:2001
Sulfur content	mg/kg	BAS EN ISO 20846:2004
Copper strip corrosion (3h at 50°C)	Stepen	BAS ISO 2160:1998
Aromatics content	% (v/v)	BAS ASTM D 1319:2009
Distillation	-	BAS EN ISO 3405:2012
- start	°C	
- 5% (v/v)	°C	
- 10% (v/v)	°C	
- 20% (v/v)	°C	
- 30% (v/v)	°C	
- 40% (v/v)	°C	
- 50% (v/v)	°C	
- 60% (v/v)	°C	
- 70% (v/v)	°C	
- 80% (v/v)	°C	
- 90% (v/v)	°C	
- 95% (v/v)	°C	
End of distillation	°C	
residue	% (v/v)	
- at 70°C	% (v/v)	
- at 100°C	% (v/v)	
- at 150°C	% (v/v)	
- at 180°C	% (v/v)	
Vapor pressure (DVPE)	kPa	BAS EN 13016-1:2009
Benzene content	%(v/v)	BAS EN 12177:1998